

VT-7M2DX

RoHS FC CE CCC

GSM Smart Alarm System with LCD Screen & Touch Keypad

NEW



FEATURES

- Touch keypad and LCD display with clock and calendar;
- GSM and land line (PSTN) dual network alarm;
- 5 user alarm phone numbers (call or sms), 1 alarm center number and 1 SMS attention number;
- 30 wireless and 4 wired zones, each zone could be programmed individually;
- 10-second voice recording, arm/alarm delay, 100 alarm and status records saving;
- 1 relay output to control home appliance;
- The alarm SMS content: defense zone number + sensor name;
- SMS alert for arm/ disarm, external power off/recovery, phone line failure,
- SMS alert for main panel battery low power, sensors low power;
- Support Ademco contact ID. Information could be upload to the alarm center;
- Compatible with all our accessories;
- Support Ding-dong doorbell function.

TECHNICAL PARAMETERS

Input voltage: DC12V/ 1.2A	Standby time: 16hrs
Standby current: <50mA	Recharging time: 12hrs
Alarming current: <500mA	Working Temperature: 10~+40
GSM band: 850/900/1800/1900MHz	Humidity: ≤90% (no fog)
Wireless frequency: 315/433/868MHz, PT2262 (default: 433)	Wireless detectors: 30pcs
Backup battery: 3.7V/ 1200mAh rechargeable battery	Wire detectors: 4 pcs



VT TECH

1784 Sunnydale Ave., Simi Valley, CA 93063
Phone: (805) 520-3159 www.vttech.com

Copyright © 2003 VT TECH Corp. All rights reserved.
HomeSafe™, VT TECH and VT TECH's logos are trademarks of VT TECH Corp.
All other company and product names may be trademarks of their respective owners.