

## VT-G992E

RoHS FC CE CCC

### Telephone and GSM Home Alarm System with LED display



#### FEATURES

- 99 wireless zones and 2 wire zones
- LED zones display
- Optional Multi modes zone settings
- Password protection
- 10 seconds personal voice recording messages
- Can store 6 groups of telephone numbers
- Wireless learning code
- Programmable alarm sound On/Mute
- Programmable alarm time
- Last status record after powered off
- Remote control arm/disarm/listen-in telephone
- Backup battery
- Wireless learning coding, compatible with 2262 or 1527 chip sensors.

#### TECHNICAL PARAMETERS

Input voltage: DC12V/ 1.2A	Standby time: 16hrs
Standby current: <50mA	Recharging time: 12hrs
Alarming current: <500mA	Working Temperature: 10~+40
GSM frequency 900Mhz/10800Mhz/1900Mhz	Humidity: =90% ( no fog)
Wireless frequency: 315/433/868MHz, PT2262 (default: 433)	Wireless detectors: 99
Backup battery: 3.7V/ 1200mALi rechargeable battery	Wire detectors: 2



**VT TECH**

1784 Sunnydale Ave., Simi Valley, CA 93063  
Phone: (805) 520-3159 www.vttech.com

Copyright © 2003 VT TECH Corp. All rights reserved.  
HomeSafe™, VT TECH and VT TECH's logos are trademarks of VT TECH Corp.  
All other company and product names may be trademarks of their respective owners.